



DRIED SAND

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name DRIED SAND

Supplier Name COCKBURN CEMENT LIMITED ABN 50 008 673 470

Address PO Box 38, Hamilton Hill, WA 6963

Manufacturing Munster Works, Lot 242 Russell Road East, Munster, WA 6166

Plant Kwinana Works, Leath Road, Kwinana WA 6167

Telephone 08 9411 1111

Emergency Bus Hrs 08 9411 1111

Email orders@cockburncement.com.au

Web Site <u>www.cockburncement.com.au</u> & <u>www.swancement.com.au</u>

Synonym(s) PAVING SAND, SAND

Use(s) Gap filling or paving, eg roadways, areas of heavy traffic movement, high wind areas,

areas where sand/cement joints would stain the paver.

2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria. Not classified as a dangerous good by the criteria of the ADG code, IMDG or IATA.

GHS Classifications

Skin Corrosion/Irritation:Category 2Serious Eye Damage / Eye Irritation:Category 1Specific Target Organ Systemic Toxicity (Repeated Exposure):Category 2

SIGNAL WORD Pictograms

WARNING



Hazard statements

H319 Causes eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to lungs and respiratory tract through prolonged or repeated

exposure.

Prevention statements

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

UN NoNone AllocatedHazchem CodeNone AllocatedPkg GroupNone AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedEPGNone Allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS





DRIED SAND

Being a sand based product there is a risk that the 'Respirable Crystalline Quartz' (RCQ) content may be hazardous to human health. While the product is wet and being applied the amount of airborne RCQ will be reduced but it is strongly advised that proper PPE is worn to minimize the possibility of inhalation. Once dry any residues, grinding or strong abrasive forces on the finished product may reintroduce RCQ into the air so caution should be taken.

Ingredient	Formula	Conc.	CAS No.
CRYSTALLINE SILICA (QUARTZ)	SiO ₂	<99.9%	14808-60-7
ADDITIVES	Not Available	<1%	-

^{*}Aggregates used may be siliceous.

4. FIRST AID MEASURES

Eye Flush thoroughly with flowing water for at least 15 minutes. Seek medical attention if

symptoms persist.

Inhalation Remove from dusty area to fresh air. If symptoms persist, seek medical attention.

Skin Wash off skin thoroughly with water. A shower may be required.

Ingestion Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute

stomach contents. If symptoms persist, seek medical attention.

Advice to Doctor Treat symptomatically.

First Aid Facilities Eye wash station.

Additional Information - Aggravated Medical Conditions

Inhalation Over exposure resulting from prolonged and repeated inhalation of dust containing

crystalline silica can cause bronchitis, silicosis (scarring of the lung.) It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scaring of the lung) and lung cancer in

persons exposed to crystalline silica.

Skin Prolonged and repeated skin contact may cause abrasions.

5. FIRE FIGHTING

Flammability
Fire and Explosion
Extinguishing
Hazchem Code

Non-flammable. Does not support combustion of other materials.

No fire or explosion hazard exists.

Non-flammable; use suitable extinguishing agent for surrounding fire.

None.

6. ACCIDENTAL RELEASE MEASURES





DRIED SAND

Spillage Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation

> risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or

reuse. Avoid generating dust.

Follow safety requirements for personal protection under Section 8 Exposure **Emergency**

Procedures Controls/Personal Protection.

HANDLING AND STORAGE

Store off the floor in the original bags in a cool, dry, well ventilated area, removed from Storage

excessive moisture and heat. Ensure packages are adequately labelled, protected from

physical damage and sealed when not in use.

Dried Sand is supplied in 20 bags. Recognised local safe lifting methods should be used. Handling

> Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking, and smoking in contaminated

areas.

Property/ **Environmental** Refer to Section 13.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation

hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels

below the recommended exposure standard.

Exposure SILICA, CRYSTALLINE - QUARTZ (14808-60-7) **Standards**

ES-TWA: 0.05 mg/m³ (Respirable Dust).

Under Model WHS Law adopted in most Australian jurisdictions.

PPE Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear

a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying

Respirator (PAPR) with Class P3 filter.







Solubility (water)

Specific Gravity

Insoluble

2.7 Average

Not Available

Non Flammable

PHYSICAL AND CHEMICAL PROPERTIES 9.

Appearance Yellow sand Odour Odourless pН Approximately 7 **Vapour Pressure** Not Available Not Available **Vapour Density Boiling Point** Not Available **Melting Point** Not Available **Evaporation Rate**

1,450 kg/m³ (approximately)

Bulk Density Particle Size < 1 mm

Flammability Flash Point Not Relevant **Upper Explosion Limit** Not Relevant **Lower Explosion Limit** Not Relevant **Autoignition** Not Available Not Available

% Volatiles

Temperature

STABILITY AND REACTIVITY 10.

Status: Approved Dep	ot: Sales & Marketing	Revision: 2.0	Issued: 6 April 2021	Supersedes: R1 October 2016	Page 3 of 6





DRIED SAND

Chemical Stability Chemically stable.

Conditions to Avoid None.

Incompatible Materials None.

Decomposition

Products

Unlikely to evolve toxic gases when heated to decomposition.

Hazardous Reactions None.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity High chronic toxicity. Associated with prolonged exposure to high potentially respirable

dust levels.

Eye Irritant upon contact with dust. Over exposure may result irritation and lacrimation.

Inhalation Long term exposure can lead to irritation in the nose and throat. Prolonged and repeated

inhalation of respirable silica may result in silicosis. It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scaring of the lung) and lung cancer in persons

exposed to crystalline silica.

Skin Irritating to the skin. Prolonged and repeated contact may result in skin rash, abrasions,

and dermatitis.

Ingestion This product is biologically inert. However, ingestion may result in gastrointestinal irritation

due to the dusts mechanical action.

Mutagenicity Insufficient data available for this product to classify as a mutagen.

Carcinogenicity Dried Sand is not classified as a carcinogen by NOHSC. Crystalline silica is classified as

carcinogenic to humans (IARC Group 1), however due to low levels present and product

application, the criteria for classification is not met.

12. ECOLOGICAL INFORMATION

Toxicity Product is inert when mixed with water. This product is non-toxic to aquatic life forms.

Persistence & Degradability Product is persistent and would have a low degradability.

Mobility in soil A low mobility would be expected in a landfill situation.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil

to prevent dust generation and dispose of to an approved landfill site. Contact the

manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater

drains.

14. TRANSPORT INFORMATION





DRIED SAND

Not classified as a dangerous good by the criteria of the ADG Code.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

Shipping Name None Allocated

UN No None Allocated Hazchem Code None Allocated Pkg Group None Allocated DG Class None Allocated Subsidiary Risk(s) None Allocated EPG None Allocated

15. REGULATORY INFORMATION

Poison Schedule AICS A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

mg/m³ - Milligrams per cubic metre

ppm - Parts Per Million

ES-TWA - Exposure Standard - Time Weighted Average

CNS - Central Nervous System NOS - Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, $\frac{1}{2}$

where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number - used to uniquely identify chemical

compounds.

IARC – International Agency for Research on Cancer.

Report Status

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.





DRIED SAND

While the information in this Safety Data Sheet has been prepared in good faith, Cockburn Cement Limited does not warrant that the information is accurate, complete, or up to date.

Contact Point

For further information on this product contact:

Telephone: Office hours 08 9411 1111

Web site: www.cockburncement.com.au

Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

08 9411 1111 or www.cockburncement.com.au or www.swancement.com.au

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- Determine whether the information or product is suitable for their purpose;
- Assess and control any risks associated with the information or product; and
- Obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Cockburn Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this Safety Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic
 loss (including but not limited to any loss of actual or anticipated profits, revenue,
 savings, production, business, opportunity, access to markets, goodwill, reputation,
 publicity, or use) arising from any use of or reliance on any information in this Safety
 Data Sheet.