

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	HYDRATED LIME
Supplier Name	COCKBURN CEMENT LIMITED ABN 50 008 673 470
Address	PO Box 38, Hamilton Hill, WA 6963
Manufacturing Plant	Munster Works, Lot 242 Russell Road East, Munster, WA 6166 Kwinana Works, Leath Road, Kwinana, WA 6167
Telephone	08 9411 1111
Emergency	Bus Hrs 08 9411 1111
Email	orders@cockburncement.com.au
Web Site	www.cockburncement.com.au & www.swancement.com.au
Synonym(s)	Hylime, Marvelime, Industrial Hydrated Lime, Premium Hydrated Lime, Chemical Hydrated Lime, Calcium Hydroxide, Slaked Lime.
Use(s)	Applications such as neutralising agent in water and sewage treatment, a binder in mortars and renders, soil stabilisation and maintaining alkaline conditions for mineral processing.

2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria.
Only classified as a dangerous good by the criteria of the ADG code when transported by air.

GHS Classifications

Skin Corrosion/Irritation:	Category 2
Serious Eye Damage / Eye Irritation:	Category 1
Specific Target Organ Systemic Toxicity (Repeated Exposure):	Category 3

SIGNAL WORD

WARNING

Pictograms



Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Prevention statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before re-use.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--



UN No	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
DG Class	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
CALCIUM HYDROXIDE	Ca(OH) ₂	65 - 75%	1305-62-0
MAGNESIUM HYDROXIDE	Mg(OH) ₂	3.5 - 5%	1309-42-8
CRYSTALLINE SILICA (QUARTZ)	SiO ₂	0.5 - 3%	14808-60-7
ALUMINIUM OXIDE	Al ₂ O ₃	0 - 1.5%	1344-28-1
IRON (III) OXIDE	Fe ₂ O ₃	0 - 1%	1309-37-1
LIMESTONE	CaCO ₃	0 - 2%	1317-65-3

* Loss on Ignition accounts for missing concentration

4. FIRST AID MEASURES

Eye	Flush thoroughly with flowing water for at least 15 minutes. Seek medical attention if symptoms persist.
Inhalation	Remove from dusty area to fresh air. If symptoms persist, seek medical attention.
Skin	Wash thoroughly with water. Immediately remove all contaminated clothing and footwear. Seek medical attention if symptoms develop.
Ingestion	Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach contents. If symptoms develop, seek medical attention.
Advice to Doctor	Treat symptomatically. Contact Poisons Information Centre (131126 Australia wide).
First Aid Facilities	Eye wash station.

Additional Information - Aggravated Medical Conditions

Inhalation	Over exposure resulting from prolonged and repeated inhalation of dust containing crystalline silica (found in this product below the reportable limit) can cause bronchitis, silicosis (scarring of the lung.) It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scarring of the lung) and lung cancer in persons exposed to crystalline silica.
Skin	Irritating to the skin. Prolonged and repeated skin contact with Lime Kiln Dust can cause irritant dermatitis or alkaline burns.
Eye	Irritating to the eye. If a large volume of lime dust (or slurry) is splashed into the eye alkaline burns can cause permanent damage.



5. FIRE FIGHTING

Flammability	Non flammable. Does not cause dust explosions. Violent reaction with maleic anhydride, nitroethane, nitromethane, nitroparaffin, nitropropane, phosphorous and oxidants.
Fire and Explosion	Non flammable. No fire or explosion hazard exists.
Extinguishing	Non flammable.
Hazchem Code	None.

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust. Lime Kiln Dust should be slowly hydrated by SLOW addition to water then neutralised with dilute Hydrochloric Acid e.g. 6M, before disposal.
Emergency Procedures	Follow safety requirements for personal protection under Section 8 Exposure Controls/ Personal Protection.

7. HANDLING AND STORAGE

Storage	Concrete or steel bins and silos or plastic lined paper sacks are the recommended forms of storage. Store in a cool, dry, well ventilated area, removed from moisture, oxidising agents (eg phosphorous oxide), acids, ethanol, interhalogens (eg chlorine trifluoride) and foodstuffs. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use. Also store removed from maleic anhydride, nitroethane, nitromethane, nitroparaffin, nitropropane, phosphorus, polychlorinated phenols and potassium nitrate.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.
Property/ Environmental	Refer to Section 13.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation	Avoid generating dust. All work with Hydrated Lime should be carried out in such a way as to minimise exposure to dust and repeated skin contact. Where dust could be generated whilst handling Hydrated Lime, use local mechanical ventilation or extraction in areas where dust could escape into the work environment. For bulk deliveries, closed pumping systems are recommended. For handling of individual bags, follow personal protection instructions if no local exhaust ventilation is available.
--------------------	---

Exposure Standards

ALUMINIUM OXIDE (1344-28-1)
 ES-TWA: 10 mg/m³ (Respirable Dust)
 CALCIUM CARBONATE (1317-85-3)
 ES-TWA: 10 mg/m³ (Respirable Dust)
 CALCIUM OXIDE (1305-78-8)
 ES-TWA: 2 mg/m³ (Respirable Dust; Alkaline)
 IRON (III) OXIDE (1309-37-1)
 ES-TWA: 5 mg/m³ (Respirable Dust)
 MAGNESIUM OXIDE (1309-48-4)
 ES-TWA: 10 mg/m³ (Respirable Dust)

SILICA, CRYSTALLINE – QUARTZ (14808-60-7)
 ES-TWA: 0.05 mg/m³ (Respirable Dust).
 Under Model WHS Law adopted in most Australian jurisdictions.

PPE Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with Class P3 filter.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	A white or off-white amorphous powder with a typical fineness of less than 1% retained on a 75 micron sieve.	Solubility (water)	Slightly
Odour	Slight Odour	Specific Gravity	2.1 to 2.3
pH	Approximately 12	% Volatiles	Not Available
Vapour Pressure	Not Available	Flammability	Non Flammable
Vapour Density	Not Available	Flash Point	Not Relevant
Boiling Point/Melting Point	Decomposes to Calcium Oxide and water @580°C	Upper Explosion Limit	Not Relevant
Evaporation Rate	Not Available	Lower Explosion Limit	Not Relevant
Bulk Density	300 - 700 kg/m ³	Autoignition Temperature	Not Available
Particle Size	99% < 75 microns		

10. STABILITY AND REACTIVITY

Reactivity Incompatible with oxidising agents (e.g. phosphorus oxide), ethanol, interhalogens (e.g. chlorine trifluoride) and acids. Also incompatible with maleic anhydride, nitroethane, nitromethane, nitroparaffin, nitropropane, phosphorus, polychlorinated phenols, and potassium nitrate.

Decomposition Products May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	No known toxicity data available for this product.
Eye	Irritant upon contact with dust. Over exposure may result in pain, redness, corneal burns, and ulceration with possible permanent damage.
Inhalation	Slightly corrosive. Irritating to the respiratory system causing coughing and sneezing. Over exposure may result in severe mucous membrane irritation and bronchitis. Crystalline silica (found in this product below the reportable limit) can cause silicosis (lung disease) with chronic over exposure, however due to low levels present and product application, adverse health effects are not anticipated.
Skin	Irritating to the skin. Contact may result in skin rash, dermatitis, and possible burns.
Ingestion	Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route.
Mutagenicity	Insufficient data available for this product to classify as a mutagen.
Carcinogenicity	Crystalline silica is carcinogenic to humans (IARC Group 1), however due to low levels present and product application, the criteria for classification is not met.
Toxicity Data	CALCIUM HYDROXIDE (1305-62-0) LD50 (Ingestion): 7300 mg/kg (mouse) MAGNESIUM HYDROXIDE (1309-43-8) LD50 (Ingestion): 8500 mg/kg (rat, mouse) SILICA, CRYSTALLINE – QUARTZ (1408-60-7) Carcinogenicity: Classified as a human carcinogen (IARC Group 1)

12. ECOLOGICAL INFORMATION

Environment	The aquatic toxicity of calcium hydroxide is due to its alkalinity. It is neutralised to calcium carbonate by absorption of atmospheric carbon dioxide and is not degraded by oxidation. Calcium hydroxide does not bioaccumulate in the environment.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer for additional information.
Legislation	Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater drains.

14. TRANSPORT INFORMATION

Only classified as a dangerous good when transported by air (ADG Code).

Transport is by rail or road in bulk or bag form.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

Shipping Name	None Allocated				
UN No	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
DG Class	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated

15. REGULATORY INFORMATION

**Poison
Schedule
AICS**

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

**Additional
Information**

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

SDS – Safety Data Sheet

mg/m³ – Milligrams per cubic metre

ppm – Parts per Million

ES-TWA – Exposure Standard - Time Weighted Average

CNS – Central Nervous System

NOS – Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number – used to uniquely identify chemical compounds.

IARC – International Agency for Research on Cancer.

ES-TWA – Exposure Standard – Time Weighted Average.

M – Moles per litre, a unit of concentration.

Report Status

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Cockburn Cement Limited does not warrant that the information is accurate, complete, or up to date.



Safety Data Sheet

HYDRATED LIME

Contact Point

For further information on this product contact:

Telephone: Office hours 08 9411 1111

Web site: www.cockburncement.com.au

Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

08 9411 1111

or

www.cockburncement.com.au or www.swancement.com.au

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- Determine whether the information or product is suitable for their purpose;
- Assess and control any risks associated with the information or product; and
- Obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Cockburn Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this Safety Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Safety Data Sheet.