

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name</b>	<b>LIME KILN DUST</b>
<b>Supplier Name</b>	<b>COCKBURN CEMENT LIMITED</b> ABN 50 008 673 470
<b>Address</b>	PO Box 38, Hamilton Hill, WA 6963
<b>Manufacturing Plant</b>	Munster Works, Lot 242 Russell Road East, Munster, WA 6166
<b>Telephone</b>	08 9411 1111
<b>Fax</b>	
<b>Emergency</b>	Bus Hrs 08 9411 1111 A/Hrs 08 9411 1111
<b>Email</b>	orders@cockburncement.com.au
<b>Web Site</b>	<a href="http://www.cockburncement.com.au">www.cockburncement.com.au</a> & <a href="http://www.swancement.com.au">www.swancement.com.au</a>
<b>Synonym(s)</b>	LKD, Lime kiln dust, Lime bypass dust.
<b>Use(s)</b>	Lime kiln dust is used primarily for industrial acid neutralisation or in agriculture for soil neutralisation.

### 2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria.  
 Only classified as a dangerous good by the criteria of the ADG code when transported by air.

#### GHS Classifications

Skin Corrosion/Irritation:	Category 2
Serious Eye Damage / Eye Irritation:	Category 1
Specific Target Organ Systemic Toxicity (Repeated Exposure):	Category 3

#### SIGNAL WORD

#### WARNING

#### Pictograms



#### Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

#### Prevention statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

#### Response statements

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P332 + P313	If skin irritation occurs: Get medical advice/attention.

#### Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

<b>UN No</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>Pkg Group</b>	None Allocated
<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated	<b>EPG</b>	None Allocated

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
LIMESTONE	CaCO <sub>3</sub>	65 - 85%	1317-65-3
CALCIUM OXIDE	CaO	10 - 20%	1305-78-8
MAGNESIUM OXIDE	MgO	2.5 - 5%	1309-48-4
CRYSTALLINE SILICA (QUARTZ)	SiO <sub>2</sub>	1 - 5%	14808-60-7

### 4. FIRST AID MEASURES

<b>Eye</b>	Flush thoroughly with flowing water for at least 15 minutes. Seek medical attention if symptoms persist.
<b>Inhalation</b>	Remove from dusty area to fresh air. If symptoms persist, seek medical attention.
<b>Skin</b>	Wash thoroughly with water. Immediately remove all contaminated clothing and footwear. Seek medical attention if symptoms develop.
<b>Ingestion</b>	Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach contents. If symptoms develop, seek medical attention.
<b>Advice to Doctor</b>	Treat symptomatically. Contact Poisons Information Centre (131126 Australia wide).
<b>First Aid Facilities</b>	Eye wash station.

#### Additional Information - Aggravated Medical Conditions

<b>Inhalation</b>	Over exposure resulting from prolonged and repeated inhalation of dust containing crystalline silica (found in this product below the reportable limit) can cause bronchitis, silicosis (scarring of the lung.) It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scarring of the lung) and lung cancer in persons exposed to crystalline silica.
<b>Skin</b>	Irritating to the skin. Prolonged and repeated skin contact with Lime Kiln Dust can cause irritant dermatitis or alkaline burns.
<b>Eye</b>	Irritating to the eye. If a large volume of lime dust (or slurry) is splashed into the eye alkaline burns can cause permanent damage.

### 5. FIRE FIGHTING

<b>Flammability</b>	Non flammable. Does not support combustion of other materials, but on contact with water or acids may generate sufficient heat to ignite surrounding materials. DO NOT USE WATER for firefighting. USE DRY CHEMICAL OR CO <sub>2</sub> TYPE EXTINGUISHERS.
<b>Fire and Explosion</b>	Non flammable. In a fire, limestone decomposes into calcium oxide and carbon dioxide and may react vigorously with acids, generating carbon dioxide – an asphyxiant.
<b>Extinguishing</b>	Non flammable.
<b>Hazchem Code</b>	None.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust. Lime Kiln Dust should be slowly hydrated by SLOW addition to water then neutralised with dilute Hydrochloric Acid e.g. 6M, before disposal.
<b>Emergency Procedures</b>	Follow safety requirements for personal protection under Section 8 Exposure Controls/ Personal Protection.

### 7. HANDLING AND STORAGE

<b>Storage</b>	Steel silos and airtight rail or road tankers are the usual forms of storage and transport. Common storage and handling equipment must NOT be used for Lime Kiln Dust. Enclosed conveyors with extraction equipment and dust collection are required for safe handling. Lime Kiln Dust must NOT come into contact with materials containing water or water of crystallisation, e.g. copper, alum, ferric sulphates. Lime Kiln Dust must be kept away from moisture, steam, acid, or acid fumes to prevent violent reactions.
<b>Handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.
<b>Property/ Environmental</b>	Refer to Section 13.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Ventilation</b>	Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.
<b>Exposure Standards</b>	<p>CALCIUM CARBONATE (1317-65-3) ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust)</p> <p>CALCIUM OXIDE (1305-78-8) ES-TWA: 2 mg/m<sup>3</sup> (Respirable Dust; Alkaline)</p> <p>MAGNESIUM OXIDE (1309-48-4) ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust)</p> <p>SILICA, CRYSTALLINE – QUARTZ (14808-60-7) ES-TWA: 0.05 mg/m<sup>3</sup> (Respirable Dust)</p>
<b>PPE</b>	Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with Class P3 filter.



### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Granular off-white amorphous powder	<b>Solubility (water)</b>	Sparsingly soluble, reacts with water
<b>Odour</b>	Slight Odour	<b>Specific Gravity</b>	3.2 to 3.4
<b>pH</b>	Approximately 12	<b>% Volatiles</b>	Not Available
<b>Vapour Pressure</b>	Not Available	<b>Flammability</b>	Non Flammable
<b>Vapour Density</b>	Not Available	<b>Flash Point</b>	Not Relevant
<b>Boiling Point</b>	2850°C	<b>Upper Explosion Limit</b>	Not Relevant
<b>Melting Point</b>	2570°C	<b>Lower Explosion Limit</b>	Not Relevant
<b>Evaporation Rate</b>	Not Available	<b>Autoignition</b>	Not Available
<b>Bulk Density</b>	750 – 1000 kg/m <sup>3</sup>		
<b>Particle Size</b>	95% < 600 microns		

### 10. STABILITY AND REACTIVITY

**Reactivity** Incompatible with hydrofluoric acid (violently) and phosphorus pentoxide. Reacts (potentially vigorously) with water generating heat and evolving calcium hydroxide.

**Decomposition** May evolve toxic gases if heated to decomposition.

### 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity** No known toxicity data available for this product.

**Eye** Irritant upon contact with dust. Over exposure may result in pain, redness, corneal burns, and ulceration with possible permanent damage.

**Inhalation** Slightly corrosive. Irritating to the respiratory system causing coughing and sneezing. Over exposure may result in severe mucous membrane irritation and bronchitis. Crystalline silica (found in this product below the reportable limit) can cause silicosis (lung disease) with chronic over exposure, however due to low levels present and product application, adverse health effects are not anticipated.

**Skin** Irritating to the skin. Contact may result in skin rash, dermatitis, and possible burns.

**Ingestion** Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route.

**Mutagenicity** Insufficient data available for this product to classify as a mutagen.

**Carcinogenicity** Crystalline silica is carcinogenic to humans (IARC Group 1), however due to low levels present and product application, the criteria for classification is not met.

**Toxicity Data**  
 CALCIUM HYDROXIDE (1305-62-0)  
 LD50 (Ingestion): 7300 mg/kg (mouse)  
 MAGNESIUM HYDROXIDE (1309-43-8)  
 LD50 (Ingestion): 8500 mg/kg (rat, mouse)  
 SILICA, CRYSTALLINE – QUARTZ (1408-60-7)  
 Carcinogenicity: Classified as a human carcinogen (IARC Group 1)

### 12. ECOLOGICAL INFORMATION

**Environment** Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal** For small amounts; VERY SLOWLY, hydrate (add water) and then neutralise with dilute hydrochloric acid (e.g. 6M HCl) to pH of 7-8. Dilute and flush to sewer or landfill. For large amounts, material can be readily recycled. Contact the manufacturer for additional information.

**Legislation** Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater drains.

### 14. TRANSPORT INFORMATION

Only classified as a dangerous good when transported by air (ADG Code).

Transport is by rail or road in bulk or bag form.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

#### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

<b>Shipping Name</b>	Calcium Oxide				
<b>UN No</b>	1910	<b>Hazchem Code</b>	4W	<b>Pkg Group</b>	111
<b>DG Class</b>	8	<b>Subsidiary Risk(s)</b>	None Allocated	<b>EPG</b>	None Allocated

### 15. REGULATORY INFORMATION

**Poison Schedule AICS** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP). All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

**Additional Information** IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

**RESPIRATORS:** In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:** The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:** It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### ABBREVIATIONS:

SDS – Safety Data Sheet

mg/m<sup>3</sup> – Milligrams per cubic metre

ppm – Parts per Million

ES-TWA – Exposure Standard - Time Weighted Average

CNS – Central Nervous System

NOS – Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# – Chemical Abstract Service Number – used to uniquely identify chemical compounds.

IARC – International Agency for Research on Cancer.

ES-TWA – Exposure Standard – Time Weighted Average.

M – Moles per litre, a unit of concentration.

### Report Status

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Cockburn Cement Limited does not warrant that the information is accurate, complete, or up to date.

### Contact Point

For further information on this product contact:

Telephone: Office hours 08 9411 1111

Web site: [www.cockburncement.com.au](http://www.cockburncement.com.au)

### Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

08 9411 1111

or

[www.cockburncement.com.au](http://www.cockburncement.com.au) or [www.swacement.com.au](http://www.swacement.com.au)

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Cockburn Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this Safety Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Safety Data Sheet.