



QUICKLIME

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name QUICKLIME

Supplier Name COCKBURN CEMENT LIMITED ABN 50 008 673 470

Address PO Box 38, Hamilton Hill, WA 6963

Manufacturing Plant Munster Works, Lot 242 Russell Road East, Munster, WA 6166

Dongara Works, Kailis Drive, Dongara, WA 6525

Telephone 08 9411 1111

Emergency Bus Hrs 08 9411 1111

Email orders@cockburncement.com.au

Web Site www.cockburncement.com.au & www.swancement.com.au &

Synonym(s) CALCIUM OXIDE, CALCIUM MONOXIDE, UNSLAKED LIME, BURNT LIME, ROCK LIME,

FLUXING LIME.

Use(s) Quicklime is used as a flux in the steel industry and in the production/recovery of

aluminium, magnesium, uranium gold and silver. It is used to make chemicals such as sodium alkalis, calcium hypochlorite and petrochemicals. It is used in soil stabilisation.

2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria.

Only classified as a dangerous good by the criteria of the ADG code when transported by air.

GHS Classifications

Skin Corrosion/Irritation:

Serious Eye Damage / Eye Irritation:

Specific Target Organ Systemic Toxicity (Repeated Exposure):

Category 2

Category 1

Category 3

SIGNAL WORD Pictograms

WARNING



Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Prevention statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician. P332 + P313 If skin irritation occurs: Get medical advice/attention.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.





QUICKLIME

UN No 1910 Hazchem Code 4W Pkg Group III

DG Class 8 Subsidiary Risk(s) None Allocated EPG None Allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
CALCIUM OXIDE	CaO	80 - 90%	1305-78-8
MAGNESIUM OXIDE	MgO	4.5 - 5.5%	1309-48-4
CRYSTALLINE SILICA (QUARTZ)	SiO ₂	1 - 5%	14808-60-7
LIMESTONE	CaCO ₃	0 - 2%	1317-65-3
ALUMINIUM OXIDE	Al_2O_3	0 - 1.5%	1344-28-1
IRON (III) OXIDE	Fe ₂ O ₃	0 - 1%	1309-37-1

4. FIRST AID MEASURES

Eye Flush thoroughly with flowing water for at least 15 minutes and medical attention if

symptoms persist. If a lime slurry is splashed into the eyes flush thoroughly for 15 minutes

then seek urgent medical attention.

Inhalation Remove from dusty area to fresh air. If s ymptoms persist, seek medical attention.

Skin Promptly wipe material off skin being sure not to generate dust. Immediately remove all

contaminated clothing and footwear. Wash skin thoroughly with copious amounts of

water.

Ingestion Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute

stomach contents. If symptoms persist, seek medical attention.

Advice to Doctor Treat symptomatically. Contact Poisons Information Centre (131126 Australia wide).

First Aid Facilities Eye wash station.

Additional Information - Aggravated Medical Conditions

Inhalation Inhalation of dust through prolonged, repeated exposure can cause membrane irritation,

bronchitis, pneumonia, silicosis (scarring of the lung.) It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scaring of the lung) and lung cancer in those

exposed to crystalline silica.

Skin Irritating to the skin. Prolonged and repeated skin contact with Quicklime can cause

irritant dermatitis.

Eye Irritating to the eye. If a large volume of lime dust (or slurry) is splashed into the eye

alkaline burns can cause permanent damage.

5. FIRE FIGHTING

Flammability Not flammable. Does not support combustion of other materials, but on contact with

water or acids may generate sufficient heat to ignite surrounding materials. DO NOT USE

WATER for fire fighting. USE DRY CHEMICAL OR CO₂ TYPE EXTINGUISHERS.

Fire and Explosion Non flammable. No fire or explosion hazard exists.

Extinguishing Non flammable.





Safety Data Sheet OUICKLIME

Hazchem Code

None Allocated.

6. ACCIDENTAL RELEASE MEASURES

Spillage

If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust. Lime Kiln Dust should be slowly hydrated by SLOW addition to water then neutralised with dilute Hydrochloric Acid e.g. 6M, before disposal.

Emergency Procedures

Follow safety requirements for personal protection under Section 8 Exposure Controls/

Personal Protection.

7. HANDLING AND STORAGE

Storage

Steel silos and airtight rail or road tankers are the usual forms of storage and transport. Common storage and handling equipment must NOT be used for Quicklime. Enclosed conveyors with extraction equipment and dust collection are required for safe handling. Quicklime must NOT come into contact with materials containing water or water of crystallisation, eg copper, alum, ferric sulphates. Quicklime must be kept away from moisture, steam, acid or acid fumes to prevent violent reactions.

Handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

Property/ Environmental

Refer to Section 13.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation

Avoid generating dust. All work with Quicklime should be carried out in such a way as to minimise exposure to dust and repeated skin contact. Where dust could be generated whilst handling Quicklime, use local mechanical ventilation or extraction in areas where dust could escape into the work environment. For bulk deliveries, closed pumping systems are recommended.

Exposure Standards

ALUMINIUM OXIDE (1344-28-1)

ES-TWA: 10 mg/m³ (Respirable Dust)
CALCIUM CARBONATE (1317-85-3)
ES-TWA: 10 mg/m³ (Respirable Dust)

CALCIUM OXIDE (1305-78-8)

ES-TWA: 2 mg/m³ (Respirable Dust; Alkaline)

IRON (III) OXIDE (1309-37-1)

ES-TWA: 5 mg/m³ (Respirable Dust)

MAGNESIUM OXIDE (1309-48-4)

ES-TWA: 10 mg/m³ (Respirable Dust)
SILICA, CRYSTALLINE – QUARTZ (14808-60-7)
ES-TWA: 0.05 mg/m³ (Respirable Dust).

Under Model WHS Law adopted in most Australian jurisdictions.

PPE

Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with Class P3 filter.





QUICKLIME









PHYSICAL AND CHEMICAL PROPERTIES 9.

Granular off-white **Appearance** amorphous powder

Odour Slight Odour Approximately 12 рH Vapour Pressure Not Available **Vapour Density** Not Available **Boiling Point** 2850°c 2570°C **Melting Point**

Evaporation Rate 950 - 1050 ka/m³ **Bulk Density**

Solubility (water) Sparingly soluble, reacts vigorously with water

Specific Gravity 3.2 to 3.4 % Volatiles Not Available **Flammability** Non Flammable **Flash Point** Not Relevant **Upper Explosion Limit** Not Relevant **Lower Explosion Limit** Not Relevant Not Available

Autoignition Temperature

STABILITY AND REACTIVITY 10.

Reactivity Incompatible with hydrofluoric acid (violently) and phosphorus pentoxide.

(potentially vigorously) with water generating heat and evolving calcium hydroxide.

Decomposition Products

Particle Size

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

No known toxicity data available for this product. **Acute Toxicity**

Not Available

50% < 75 microns

Corrosive. Severe irritant upon contact with powder/dust. Over exposure may result in Eye

pain, redness, corneal burns, and ulceration with possible permanent damage.

Inhalation Corrosive. Over exposure to powder - dust (when mixing) may result in severe mucous

membrane irritation of nose and throat, coughing and bronchitis at high levels.

Skin Irritating and drying to skin. May cause alkaline burns and irritant or allergic dermatitis.

Ingestion Corrosive. Ingestion may result in ulceration and burns to the mouth and throat, nausea,

vomiting, abdominal pain, and diarrhoea.

Mutagenicity Insufficient data available for this product to classify as a mutagen.

Crystalline silica is carcinogenic to humans (IARC Group 1), however due to low levels Carcinogenicity

present and product application, the criteria for classification is not met.

Toxicity Data CALCIUM HYDROXIDE (1305-62-0)

LD50 (Ingestion): 7300 mg/kg (mouse) MAGNESIUM HYDROXIDE (1309-43-8)

LD50 (Ingestion): 8500 mg/kg (rat, mouse) SILICA, CRYSTALLINE - QUARTZ (1408-60-7)

Carcinogenicity: Classified as a human carcinogen (IARC Group 1)

ECOLOGICAL INFORMATION

	Status: Approved	Dept: Sales & Marketing	Revision: 2.0	Issued: 6 April 2021	Supersedes: R1 November 2016	Page 4 of 6
--	------------------	-------------------------	---------------	----------------------	------------------------------	-------------





QUICKLIME

Environment

Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts; VERY SLOWLY, hydrate (add water) and then neutralise with dilute

hydrochloric acid (e.g. 6M HCl) to pH of 7-8. Dilute and flush to sewer or landfill. For large amounts, material can be readily recycled. Contact the manufacturer for additional

information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Only classified as a dangerous good when transported by air (ADG Code).

Transport is by rail or road in bulk or bag form.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

Shipping Name Calcium Oxide

UN No 1910 Hazchem Code 4W Pkg Group 111

DG Class 8 Subsidiary Risk(s) None Allocated EPG None Allocated

15. REGULATORY INFORMATION

Poison Schedule AICS A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use;





QUICKLIME

quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

SDS - Safety Data Sheet

mg/m³ - Milligrams per cubic metre

ppm - Parts per Million

ES-TWA - Exposure Standard - Time Weighted Average

CNS – Central Nervous System NOS – Not Otherwise Specified

pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 - 14,

where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number - used to uniquely identify chemical

compounds.

IARC – International Agency for Research on Cancer. ES-TWA – Exposure Standard – Time Weighted Average.

M - Moles per litre, a unit of concentration.

Report Status

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Cockburn Cement Limited does not warrant that the information is accurate, complete, or up to date.

Contact Point

For further information on this product contact:

Telephone: Office hours 08 9411 1111

Web site: www.cockburncement.com.au

Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

08 9411 1111

or

www.cockburncement.com.au or www.swancement.com.au

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- Determine whether the information or product is suitable for their purpose;
- Assess and control any risks associated with the information or product; and
- Obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Cockburn Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this Safety Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic
 loss (including but not limited to any loss of actual or anticipated profits, revenue,
 savings, production, business, opportunity, access to markets, goodwill, reputation,
 publicity, or use) arising from any use of or reliance on any information in this Safety
 Data Sheet.