

# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name GROUND GRANULATED BLAST FURNACE SLAG

Supplier Name COCKBURN CEMENT LIMITED ABN 50 008 673 470

**Address** PO Box 38, Hamilton Hill, WA 6963

Manufacturing Plant Munster Works, Lot 242 Russell Road East, Munster, WA 6166

Kwinana Works, Leath Road, Kwinana WA 6167

**Telephone** 08 9411 1111

**Emergency** Bus Hrs 08 9411 1111

**Email** orders@cockburncement.com.au

Web Site <a href="www.cockburncement.com.au">www.cockburncement.com.au</a> & <a href="www.swancement.com.au">www.swancement.com.au</a> & <a href="www.swancement.com.au">www.swancement.co

Synonym(s) GGBFS, GROUND GRANULATED BLAST FURNACE SLAG, NEAT MILLED SLAG, NMS, SLAG,

GROUND SLAG, GRANULATED BLAST FURNACE SLAG, GBFS.

**Use(s)** supplementary cementitious material (SCM) that is used in the manufacture of cementitious

binders and as a partial replacement for Portland Cement in concrete and other similar products. Also used in glass making, construction sand, and as a agricultural soil conditioner.

### 2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria. Not classified as a dangerous good by the criteria of the ADG code, IMDG or IATA.

#### **GHS Classifications**

Specific target organ toxicity (repeated exposure)

Skin irritation

Eye damage

Specific target organ toxicity (single exposure)

category 1

category 1

category 1

category 2

category 1

category 3

# SIGNAL WORD Pictograms

#### DANGER



### **Hazard statements**

H372 Causes damage to organs (lungs) through prolonged or repeated exposure if inhaled

H315 Causes skin irritation

H318 Causes serious eye damage H335 May cause respiratory irritation

#### **Prevention statements**

P201 Obtain special instructions prior to use.

P202 Do not handle until all safety instructions have been read and understood.

P260 Do not breathe dust.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response statements

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P308 + P313 If exposed of concerned: Get medical advice/attention.



None

Allocated

# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

**Disposal statements** 

P501 Dispose of contents/container in accordance with relevant regulations.

UN No None Allocated Hazchem Code None Allocated Pkg Group

DG Class None Allocated Subsidiary Risk(s) None Allocated EPG None Allocated

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient                    | Formula                             | Conc.  | CAS No.    |
|-------------------------------|-------------------------------------|--------|------------|
| GRANULATED BLAST FURNACE SLAG | Not Available                       | > 90%  | 65996-69-2 |
| GYPSUM                        | CaSO <sub>4</sub> 2H <sub>2</sub> O | 2 - 5% | 10101-41-4 |
| CRYSTALLINE SILICA (QUARTZ)   | SiO <sub>2</sub>                    | <1%    | 14808-60-7 |
| CHROMIUM (VI) HEXAVALENT      | Cr <sup>6+</sup>                    | Trace  | 18540-29-9 |

### 4. FIRST AID MEASURES

**Eye** Flush thoroughly with flowing water for at least 15 minutes. Seek medical attention if

symptoms persist.

**Inhalation** Remove from dusty area to fresh air. If symptoms persist, seek medical attention.

**Skin** Remove heavily contaminated clothing immediately. Wash off skin thoroughly with water.

A shower may be required. Seek medical attention for persistant irritation or burning of the

skin

Ingestion Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute

stomach contents. If symptoms persist, seek medical attention.

**Advice to Doctor** Treat symptomatically.

# **Additional Information - Aggravated Medical Conditions**

Inhalation Over exposure resulting from prolonged and repeated inhalation of dust containing

crystalline silica can cause bronchitis, silicosis (scarring of the lung.) It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scaring of the lung) and lung cancer in

persons exposed to crystalline silica.

**Skin** Prolonged and repeated skin contact with cement in wet concrete, mortars and slurries may

result in irritant dermatitis.

# 5. FIRE FIGHTING

**Flammability** Non-flammable. Does not support combustion of other materials.

**Fire and Explosion** No fire or explosion hazard exists.

**Extinguishing** Non-flammable; use suitable extinguishing agent for surrounding fire.

Hazchem Code None.

Status: Approved Dept: Sales & Marketing Revision: 5.0 Issued: 20 Sept 2024 Supersedes: R4 May 2023 Page 2 of 6



# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

CEMENT

### 6. ACCIDENTAL RELEASE MEASURES

Spillage If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles,

PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating

dust.

**Emergency** Follow safety requirements for personal protection under Section 8 Exposure

**Procedures** Controls/Personal Protection.

# 7. HANDLING AND STORAGE

Storage Store off the floor in the original bags in a cool, dry, well ventilated area, removed from

excessive moisture and heat. Ensure packages are adequately labelled, protected from

physical damage and sealed when not in use.

**Handling** Before use carefully read the product label. Use of safe work practices are recommended to

avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing

hands before eating. Prohibit eating, drinking, and smoking in contaminated areas.

Property/ Environmental Refer to Section 13.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation** Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation

hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels

below the recommended exposure standard.

**Exposure** GROUND GRANULATED BLAST FURNACE SLAG (65996-69-2)

**Standards** ES-TWA: 10mg/m³ (Respirable Dust)

GYPSUM (10101-41-4)

ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust) SILICA, CRYSTALLINE – QUARTZ (14808-60-7) ES-TWA: 0.05 mg/m<sup>3</sup> (Respirable Dust).

Under Model WHS Law adopted in most Australian jurisdictions.

CHROMIUM (VI) HEXAVALENT (18540-29-9)

ES-TWA: 0.05 mg/m<sup>3</sup> (Chromium VI compounds)

PPE Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact,

wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying

Respirator (PAPR) with Class P3 filter.







## 9. PHYSICAL AND CHEMICAL PROPERTIES



# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

Fine white powder Solubility Slight, **Appearance** (water) hardens on

mixing with

water

Not Available

2.8 to 3.2 Odour Odourless Specific Gravity Not Available Approximately 12 % Volatiles pН Not Available **Flammability** Vapour Non

Flammable

**Pressure** Vapour Not Available Flash Point Not Relevant **Density** 

**Boiling Point** Not Available Not Relevant **Upper Explosion** 

Limit

Autoignition

Lower Not Relevant

**Melting Point** > 1200°C **Explosion Limit** 

**Temperature** Rate **Bulk Density** 1200 - 1600 kg/m3

**Particle Size** 20 - 40% of particles are < 7 μm (Respirable Range)

#### STABILITY AND REACTIVITY 10.

**Chemical Stability** Chemically Stable

**Conditions to Avoid** Keep free of moisture

**Incompatible** Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric

Not Available

**Materials** and interhalogens (e.g. chlorine trifluoride). Water contact may increase product

**Decomposition** 

**Evaporation** 

**Products** 

Unlikely to evolve toxic gases when heated to decomposition.

#### **Hazardous Reactions None**

#### **TOXICOLOGICAL INFORMATION** 11.

**Acute Toxicity** No known toxicity data available for this product.

Irritant upon contact with dust. Over exposure may result in pain, redness, corneal burns, Eye

and ulceration with possible permanent damage.

**Inhalation** Irritating to the respiratory system, causing coughing and sneezing. Over exposure may

> result in severe mucous membrane irritation and bronchitis. Crystalline silica can cause silicosis (lung disease) with chronic over exposure, however due to low levels present and

product application, adverse health effects are not anticipated.

Skin Irritating to the skin. Prolonged and repeated contact with powder or wetted form may

result in skin rash, dermatitis, and sensitisation.

**Ingestion** Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and

abdominal pain. Due to product form, ingestion is not considered a likely exposure route.

Mutagenicity Insufficient data available for this product to classify as a mutagen.

Carcinogenicity Ground granulated blast furnace slag is not classified as a carcinogen by NOHSC. Crystalline

silica is carcinogenic to humans (IARC Group 1), however due to low levels present and

product application, the criteria for classification is not met.

Status: Approved Dept: Sales & Marketing Revision: 5.0 Issued: 20 Sept 2024 Supersedes: R4 May 2023 Page 4 of 6



# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

### 12. ECOLOGICAL INFORMATION

**Toxicity** Product forms an alkaline slurry when mixed with water. This product is non-toxic to aquatic

life forms when present in cured solid form.

Persistence & Degradability

Product is persistent and would have a low degradability.

**Mobility in soil** A low mobility would be expected in a landfill situation.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal** Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to

prevent dust generation and dispose of to an approved landfill site. Contact the

manufacturer for additional information.

**Legislation** Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater

drains.

### 14. TRANSPORT INFORMATION

Not classified as a dangerous good by the criteria of the ADG Code.

Transport is by rail or road in bulk or bag form.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

#### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

Shipping Name None Allocated

UN NoNone AllocatedHazchem CodeNone AllocatedPkg GroupNone AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedEPGNone Allocated

# 15. REGULATORY INFORMATION

Poison Schedule AICS A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

# 16. OTHER INFORMATION

### Additional Information

CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout, or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked, or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the



# GROUND GRANULATED BLAST FURNACE SLAG

an ADBRI company

availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### ABBREVIATIONS:

mg/m<sup>3</sup> - Milligrams per cubic metre

ppm - Parts Per Million

ES-TWA - Exposure Standard - Time Weighted Average

CNS - Central Nervous System

NOS - Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number - used to uniquely identify chemical compounds.

IARC - International Agency for Research on Cancer.

### **Report Status**

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Cockburn Cement Limited does not warrant that the information is accurate, complete, or up to date.

#### **Contact Point**

For further information on this product contact:

Telephone: Office hours 08 9411 1111

Web site: <u>www.cockburncement.com.au</u>

#### **Advice Note**

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

08 9411 1111

or

www.cockburncement.com.au or www.swancement.com.au

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- Determine whether the information or product is suitable for their purpose;
- Assess and control any risks associated with the information or product; and
- Obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Cockburn Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this Safety Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic
  loss (including but not limited to any loss of actual or anticipated profits, revenue,
  savings, production, business, opportunity, access to markets, goodwill, reputation,
  publicity, or use) arising from any use of or reliance on any information in this Safety
  Data Sheet.